

# Eaton 216380

Catalog Number: 216380

Eaton Moeller® series M22 Contact element, Screw terminals, Base fixing, 1 N/O, 24 V 3 A, 220 V 230 V 240 V 6 A M22-KC10



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Moeller® series M22 Accessory	216380
Contact element	<b>EAN</b>
	4015082163808
<b>Product Length/Depth</b>	<b>Product Height</b>
38 mm	10 mm
<b>Product Width</b>	<b>Product Weight</b>
32 mm	0.01 kg
<b>Compliances</b>	<b>Certifications</b>
CE Marked	EN 60947-5
	UL 508
	CSA Std. C22.2 No. 14-05
	IEC 60947-5
	CSA Std. C22.2 No. 94-91
	VDE
	IEC/EN 60947-5
	UL Category Control No.: NKCR
	CSA
	UL
	CSA Class No.: 3211-03
	CSA File No.: 012528
	UL File No.: E29184
	CSA-C22.2 No. 14-05
	CE
	CSA-C22.2 No. 94-91
	IEC 60947-5-1

## Amperage Rating

6A

### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

#### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

##### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

##### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

##### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

#### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

#### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.2.7 Inscriptions

Meets the product standard's requirements.

### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

## Declarations of conformity

DA-DC-00004971.pdf

DA-DC-00004975.pdf

## Desenhos

eaton-operating-pushbutton-m22-dimensions-003.eps

eaton-operating-contact-m22-contact-element-3d-drawing-003.eps

eaton-general-standards-000Z425.jpg

eaton-operating-adapter-m22-contact-element-flow-diagram-003.eps

## eCAD model

ETN.216380.edz

## Esquemas

eaton-operating-contact-m22-contact-element-wiring-diagram-002.eps

## Instruções de instalação

IL04716002Z

eaton-operating-devices-rmq-titan-m22-instruction-leaflet-il047018zu.pdf

## mCAD model

DA-CD-kontaktelement\_schraube\_boden

DA-CS-kontaktelement\_schraube\_boden

## Multimídia

RMQ small E-Stop emergency-stop button

## Relatórios de certificação

DA-DC-00004134.pdf

DA-DC-00004141.pdf

DA-DC-00004135.pdf

DA-DC-00004157.pdf

DA-DC-00004176.pdf

DA-DC-00004180.pdf

000Z425

## System overview

Pilot devices - selection aid

#### 10.4 Clearances and creepage distances

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### Electric connection type

Screw connection

#### Operating frequency

3600 Operations/h

#### Pollution degree

3

#### Climatic proofing

Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78

#### Actuating force - max

5 N

#### Ambient operating temperature - max

70 °C

#### Ambient operating temperature - min

-25 °C

#### Ambient storage temperature - max

85 °C

#### Ambient storage temperature - min

-25 °C

Equipment heat dissipation, current-dependent P<sub>vid</sub>

0 W

Force for positive opening - min

0 N

Heat dissipation capacity P<sub>diss</sub>

0 W

Heat dissipation per pole, current-dependent P<sub>vid</sub>

0.11 W

Number of contacts (change-over contacts)

0

Number of contacts (normally closed contacts)

0

Number of contacts (normally open contacts)

1

Number of switches (fault signal)

0

Connection to SmartWire-DT

No

Rated impulse withstand voltage (U<sub>imp</sub>)

6000 V AC

Contact configuration

1 NO

Color

Green

Connection type

Base fixing

Single contact

Screw connection

Mounting method

Floor fastening

Overvoltage category

III

Control circuit reliability

1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA)

1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA)

Degree of protection

IP20

#### Model

Top mounting

#### Lamp holder

None

#### Lifespan, electrical

1,200,000 Operations (at 12 V, DC-13, 2.8 A)

1,000,000 Operations (at 230 V, AC-15, 1 A)

1,600,000 Operations (at 230 V, 0.5 A)

700,000 Operations (at 230 V, AC-15, 3 A)

#### Terminal capacity (stranded)

0.5 - 2.5 mm<sup>2</sup>

#### Lifespan, mechanical

5,000,000 Operations

#### Short-circuit protection

PKZM0-10/FAZ-B6/1, Contacts, Max. short-circuit protective device, Fuseless

#### Static heat dissipation, non-current-dependent Pvs

0 W

#### Rated operational current (I<sub>e</sub>) at DC-13, 500 V

0.1 A

#### Short-circuit protection rating

Max. 10 A gG/gL, Fuse, Contacts

#### Operating torque

0.8 Nm

#### Rated insulation voltage (U<sub>i</sub>)

500 V

#### Rated operational current (I<sub>e</sub>) at AC-15, 115 V

6 A

#### Rated operational current (I<sub>e</sub>) at AC-15, 220 V, 230 V, 240 V

6 A

#### Rated operational current (I<sub>e</sub>) at AC-15, 380 V, 400 V, 415 V

4 A

#### Rated operational current (I<sub>e</sub>) at AC-15, 500 V

2 A

#### Rated operational current (I<sub>e</sub>) at DC-13, 110 V

0.6 A

#### Rated operational current (I<sub>e</sub>) at DC-13, 220 V, 230 V

0.3 A

Rated operational current (Ie) at DC-13, 24 V

3 A

Rated operational current (Ie) at DC-13, 42 V

1.7 A

Rated operational current (Ie) at DC-13, 60 V

1.2 A

Rated operational current for specified heat dissipation (In)

6 A

Terminal capacity (flexible with ferrule)

0.5 - 1.5 mm<sup>2</sup>

Terminal capacity (solid)

0.75 - 2.5 mm<sup>2</sup>

Shock resistance

30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal  
shock 11 ms



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. Todos os  
direitos reservados.

Eaton is a registered trademark.

All other trademarks are  
property of their respective  
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)